

## NOTES:

- 1. DRIVEWAY AND ACCESS ROAD WIDTHS PER DWGS FP-9 OR FP-10.
- 2. ALL RADII MUST BE MEASURED TO THE EDGE OF DRIVING SURFACE OR FACE OF ASPHALT DIKE OR CONCRETE CURB.
- 3. MAXIMUM CROSS SLOPE THROUGHOUT THE TURNOUT MUST NOT EXCEED 5% IN ANY DIRECTION.
- 4. OPTIONAL: VEHICLE OVERHANG LIMITS, DRIVING SURFACE IN THIS AREA IS NOT REQUIRED, HOWEVER SURFACE MUST BE LEVEL AND CLEAR OF ALL OBSTRUCTIONS.
- 5. VEGETATION CLEAR ZONE PER DWG FP-12 MUST BE MAINTAINED FOR CAL FIRE ACCESS.
- 6. DEAD-END ACCESS ROAD LENGTHS MUST NOT EXCEED THAT SHOWN IN TABLE 1, OR AS APPROVED BY CALFIRE.



COUNTY OF SAN LUIS OBISPO FIRE DEPARTMENT / CAL FIRE

TURNAROUND MODIFIED HAMMERHEAD FOR PRIVATE DRIVEWAYS & ACCESS ROADS

Revised:

APRIL 2023

Drawing PP \_ 3